



SASU DIFFUSIONS AROMATIQUES

Edité le : 30/04/2025 par AC

558 allée des Parfums

Parc d'activités "Les Hauts de Grasse"

06530 SAINT-CEZAIRE-SUR-SIAGNE

Tel : +33 (0)4 93 60 82 82 Fax : +33 (0)4 93 60 82 79

Site : www.diffusions-aromatiques.fr Mail : contact@diffusions-aromatiques.fr

Technical Data Sheet

BUTYL ACETATE

Manufacture SASU DIFFUSIONS AROMATIQUES

Reference : BUTYL ACETATE

CARACTERISTIQUES GENERALES

<i>FORMULA :</i>	C6 H12 O2
<i>CHEMICAL IDENTIFICATION :</i>	N-butyl acetate
<i>GRADE :</i>	Synthetic
<i>PRODUCT ORIGIN :</i>	On request, according to each batch
<i>INCI NAME :</i>	BUTYL ACETATE
<i>Storage conditions :</i>	Keep in tightly closed container in a cool and dry place, protected from light.
<i>SHELF LIFE :</i>	24 months in below conditions, after this time it can be used after control.
<i>REVISION DATE :</i>	30/09/2023

CARACTERISTIQUES ORGANOLEPTIQUES

<i>Color :</i>	Colorless
<i>ODOR :</i>	Ethereal ; fruity ; pineapple ; banana
<i>Appearance :</i>	Liquid
<i>Solubility(ies) :</i>	Insoluble in water, soluble in ethanol

CARACTERISTIQUES PHYSICO-CHIMIQUES

<i>Relative density (d20/20) :</i>	[0.876 ; 0.890]
<i>Flash point :</i>	23°C
<i>Refractive index to 20°C :</i>	[1.389 ; 1.399]
<i>ASSAY (%GC) :</i>	Min. 97%
<i>ACID VALUE (mg KOH/g) :</i>	Max. 2.0 mgKOH/g
<i>OPTICAL ROTATION (°) :</i>	ND
<i>MELTING POINT (capillarity) °C :</i>	ND
<i>PEROXIDE INDEX (mmol/O2) :</i>	On request - if applicable

REGULATORY DATA

<i>FOOD GRADE :</i>	Yes, according to batches (on request)
<i>SOLVENTS (%) :</i>	/
<i>ADDITIVES :</i>	/
<i>ETHICAL INFORMATION :</i>	KOSHER / HALAL (on request)
<i>TERPENOIDES :</i>	Does not contains Camphor, Eucalyptol, Menthol
<i>VOC RATE :</i>	100%
<i>RESIDUAL EXTRACTION SOLVENT :</i>	/
<i>ANTIOXIDANTS :</i>	/

BUTYL ACETATE

PRESERVATIVE : /
% renewable carbon : ND

Description

MOLECULAR WEIGHT : 116.16

LEGISLATION :

COE : 194
FLAVIS : 09.004
JECFA : 0127
FEMA : 2174
TARIF DOUANIER / HS CODE : 29153300
REACH registration : 01-2119485493-29-****
EINECS : 204-658-1
C.A.S : 123-86-4