



SASU DIFFUSIONS AROMATIQUES

Edité le : 08/01/2026 par MCL

SAS DIFFUSIONS AROMATIQUES - VIDARA Groupe

558 allée des Parfums

Parc d'activités "Les Hauts de Grasse"

06530 SAINT-CEZAIRE-SUR-SIAGNE

Tel : +33 (0)4 93 60 82 82 Fax : +33 (0)4 93 60 82 79

Site : www.diffusions-aromatiques.fr Mail : contact@diffusions-aromatiques.fr

Technical Data Sheet

GURJUM RECTIFIED OIL (GURJUNENE)

Manufacture SASU DIFFUSIONS AROMATIQUES

Reference : GURJUM RECTIFIED OIL (GURJUNENE)

CARACTERISTIQUES GENERALES

GRADE :	Natural
INCI NAME :	DIPTEROCARPUS TURBINATUS BALSAM OIL
MODE OF OBTAINING :	Tree exudate harvested and collected by heating the tree trunk. Further redistilled (steam distillation) to obtain a lighter color (without residues)
BOTANICAL NAME :	Dipterocarpus turbinatus - Gurjunene quality
PRODUCT ORIGIN :	On request, according to each batch
SHELF LIFE :	24 months in below conditions, after this time it can be used after control.
Storage conditions :	Keep in tightly closed container in a cool and dry place, protected from light.
REVISION DATE :	01/05/2026

CARACTERISTIQUES ORGANOLEPTIQUES

Color :	Pale yellow to dark yellow
ODOR :	Balsamic ; woody ; earthy ; warm
Appearance :	Liquid
Solubility(ies) :	Insoluble in water, soluble in ethanol

CARACTERISTIQUES PHYSICO-CHIMIQUES

Relative density (d _{20/20}) :	[0.919 ; 0.970]
Refractive index to 20°C :	[1.498 ; 1.507]
Flash point :	105° C
OPTICAL ROTATION (°) :	@25°C : -170° / -85°
PEROXIDE INDEX (mmol/O ₂) :	On request - if applicable
MELTING POINT (capillarity) °C :	ND

REGULATORY DATA

ETHICAL INFORMATION :	Kosher / Halal (according to batches ; on request)
FOOD GRADE :	NO
RESIDUAL EXTRACTION SOLVENT :	/
ADDITIVES :	/
SOLVENTS (%) :	/
ANTIOXIDANTS :	/
TERPENOIDES :	Does not contains Camphor, Eucalyptol, Menthol
PRESERVATIVE :	/
% renewable carbon :	100%

GURJUM RECTIFIED OIL (GURJUNENE)

VOC SWISS : <1%

LEGISLATION :

EINECS : 232-444-8

EC NUMBER (REACH) : 947-839-7

REACH registration : Exempted (low tonnage <1t/year)

TARIF DOUANIER / HS CODE : 33012949

C.A.S : 8030-55-5