



SASU DIFFUSIONS AROMATIQUES

Edité le : 07/10/2025 par MCL

558 allée des Parfums

Parc d'activités "Les Hauts de Grasse"

06530 SAINT-CEZAIRE-SUR-SIAGNE

Tel : +33 (0)4 93 60 82 82 Fax : +33 (0)4 93 60 82 79

Site : www.diffusions-aromatiques.fr Mail : contact@diffusions-aromatiques.fr

Technical Data Sheet

OPOPONAX RESINOID

Manufacture SASU DIFFUSIONS AROMATIQUES

Reference : OPOPONAX RESINOID

CARACTERISTIQUES GENERALES

<i>MODE OF OBTAINING :</i>	Obtained by solvent extraction of Opoponax gum (Commiphora erythraea glabrescens fam. Umbelliferae)
<i>INCI NAME :</i>	COMMIPHORA ERYTHREA GLABRESCENS GUM EXTRACT
<i>GRADE :</i>	Natural
<i>BOTANICAL NAME :</i>	Commiphora erythraea glabrescens
<i>PRODUCT ORIGIN :</i>	On request, according to each batch
<i>INCI NAME OF CHINA FDA :</i>	/
<i>SHELF LIFE :</i>	24 months in below conditions, after this time it can be used after control.
<i>Storage conditions :</i>	Store the products in tightly closed cans in a cool, dry place, away from light.
<i>REVISION DATE :</i>	21/02/2024

CARACTERISTIQUES ORGANOLEPTIQUES

<i>Appearance :</i>	Solid
<i>Color :</i>	Brown to reddish brown
<i>ODOR :</i>	Warm ; balsam ; woody
<i>Solubility(ies) :</i>	ND

CARACTERISTIQUES PHYSICO-CHIMIQUES

<i>Flash point :</i>	> 100°C
<i>Refractive index to 20°C :</i>	NA
<i>Relative density (d20/20) :</i>	NA
<i>OPTICAL ROTATION (°) :</i>	ND
<i>PEROXIDE INDEX (mmol/O2) :</i>	On request - if applicable
<i>MELTING POINT (capillarity) °C :</i>	ND
<i>SPECIFIC GRAVITY (25°C g/cm3) :</i>	/

REGULATORY DATA

<i>ETHICAL INFORMATION :</i>	KOSHER / HALAL (according to batches ; on request)
<i>FOOD GRADE :</i>	According to batches, on request
<i>RESIDUAL EXTRACTION SOLVENT :</i>	Ethanol <1%
<i>ADDITIVES :</i>	/
<i>ANTIOXIDANTS :</i>	/
<i>SOLVENTS (%) :</i>	/
<i>PRESERVATIVE :</i>	/

OPOPONAX RESINOID

TERPENOIDES : Does not contains Camphor, Eucalyptol, Menthol
% renewable carbon : ND
VOC RATE : 1.02%

LEGISLATION :

TARIF DOUANIER / HS CODE : 33013000
REACH registration : Low tonnage exemption (manufactured or imported < 1t/year)
EINECS : 232-558-8
CAS EINECS : 9000-78-6
C.A.S : 8021-36-1